



Project Name:

Specifier:

Distributor:

Quantity:

Type:

Signature:

GR-W Series

The
Innovative
Line
of



LED Lighting Solutions

GRW Series wallwashing in low to medium ceiling heights typically found in residential, commercial or retail applications. The wall wash fixture creates consistent and even illumination from ceiling down using our proprietary Supertex™ lens. Fixture provided with LED positioned for optimal performance. The Graffiti™ fixtures provide cost effective LED lighting solutions. As the creative spirit of its name implies, Graffiti™ systems provide all the quality SLI has grown famous for over the last 25 years, but at reduced lead times, affordable price points and innovative technologies that will liberate your creative flair.

THERMAL MANAGEMENT: Proprietary high performance aluminum black heatsink for maximum LED life

WALL WASHER

SPECIFICATIONS

MOUNTING - Recessed in architectural ceiling. Butterfly brackets and Hanger bars included with housing and mounting pans.

- **RM**- Open fixture for retrofit for remodel in existing ceilings
- **IC**- Housing for new construction where insulation comes in contact with fixture
- **NIC**- Housing for new construction where IC not required
- **NP**- For New construction
- **DP**- Pan for dropped ceilings
- **BP**- Pan for metal studs
- **CP**- Chicago Plenum

HOUSING - C1/C2 Fixed housing is smaller size than Lutron/EldoLED Fixed housing (see page 3 for details)*.

TRIM - Die cast aluminum, flanged or flangeless trim with a regress bevel and overlap for flange. Available for wet locations.

*Accommodates up to 1" ceiling thickness as standard.
*(Extension Clips available upon request)

- **ZT**- for use in plaster/GWB ceilings
- **FT/FST**- for use in architectural ceilings

ELECTRICAL

- **Standard 0-10v (C1)** Dimming down to 1%
 - **TRIAC/ELV (C2)** Dimming down to 1%
 - **EldoLED 0-10v (E1)** Logarithmic Dimming down to 0.1%
 - **EldoLED Dali (E2)** Dimming down to 0.1%
 - **EldoLED 0-10v (E3) Linear Dimming down to 0.1%**
 - **Lutron Hi-lume EcoSystem 1% (LTB)** Hi-lume 1% with Fade-to-Black (former H-Series) digital EcoSystem Driver
 - **Lutron Hi-lume Premier 0.1% (LTP)** Hi-lume Premier 0.1% with Fade-to-Black digital EcoSystem
 - **EM Pack** Dimming driver with emergency battery backup
- All drivers are field replaceable*

Specifier/Installer is responsible for testing & validating compatability of any control equipment used. Additional conductors may be required depending on dimming system.



LED

- **CZ- Citizen** 2400K / 2700k / 3000 / 3500K / 4000K, 90+CRI, 50+R9
- **AD- Ambient Dim™** 3000 to 1900K / 3000 to 2200K / 2700 to 2200K, 97 CRI
- **XT- Xicato** Available on request

LENS/OPTICS - Supertex borosilicate spread lens, hinged for relamping.

FINISH - Black powder paint housing. Aperture trim available in white, black and silver as standard. White recommended for field paint matching.

WARRANTY - 5 year limited on LED and driver. See website for details.


LABELS -  US tested to UL standards 1598, Dry/Damp and Wet listings. IC/Airtight,  Supports CA Title 24 part 6 compliance meeting JA8 Requirements in many combinations. Chicago Plenum Available.





INFORMATION- TRIM




ROUND/ FLANGED




ROUND / FLANGELESS



SQUARE / FLANGED



SQUARE / FLANGELESS



PHOTOMETRICS

[*Click here to visit website for further photometric data](#)

**LED Technology rapidly changes. Please consult factory for latest specs and photometry.*

Care & Maintenance

***LED's are sensitive electronic components and should be protected from dust and debris during the installation and maintenance process.*

[**Fixture Care & Maintenance Guidelines](#)

ORDER INFO

CODE

Graffiti™ Housing

GRW

Housing

RM = Retrofit
IC = IC/Airtight
NIC = Non IC
NP = New Pan
DP = Dropped Pan
BP = Bracket Pan
CP = Chicago Plenum

Source/System Watts/Delivered lm

CZ14 = Citizen 14W / 813lm / 58LPW
CZ20 = Citizen 21W / 1102lm / 53 LPW
CZY = Citizen 21W / 1318lm / 63LPW
AD14 = Ambient Dim 15W / 526lm / 35 LPW
AD20 = Ambient Dim 21W / 826lm (AD 3019 only) / 36LPW
Based on Round. AD based on 3019 at 3k.
(See Photometrics tab on website for other values.)

Type

WW = Wall Wash

CCT

Fixed White
24 = 2400K
27 = 2700K
30 = 3000K
35 = 3500K
40 = 4000K

Ambient Dim
3019 = 3000K to 1900K
3022 = 3000K to 2200K (AD14 only)
2722 = 2700 to 2200K (AD14 only)

Driver **Lutron & EldoLED require Inverter

C1 = 0-10V dimming, 1%, 120-277v
C2 = TRIAC/ELV 2-wire, 1% 120V only (Leading/Trailing Edge)
E1 = EldoLED 0-10V Logarithmic Dim, 0.1%, 120-277v
E2 ** = EldoLED DALI, 0.1%, 120-277v
E3 = EldoLED 0-10V Linear Dim, 0.1%, 120-277v
LTB ** = Hi-lume 1% with Fade-to-Black (former H-Series) digital EcoSystem Driver, 120-277v (LDE1)
LTP ** = Hi-lume Premier 0.1% with Fade-to-Black digital EcoSystem, 120-277v (PEQ0)
EM = Emergency Pack
C1-EM = C1 Emergency Pack (0-10V dimming, 1%, 120-277v)
C2-EM = C2 Emergency Pack (TRIAC/ELV 2-wire, 1% 120V only (Leading/Trailing Edge)

Graffiti™ Trim

GRTW

Shape

RD = Round
SQ = Square

Trim

**Lens Required*




FT = Flanged
ZT = Flangeless

FST* = Flanged Shower
ZST* = Flangeless Shower

TEX2 = Extension Clips

Finish

WHT = White
BLK = Black
SLV = Silver



Lens

82A

82A = Frosted Supertex

[* CLICK HERE to view Accessories for Trims.](#)

INFORMATION- HOUSING


RETROFIT

For easy installation in existing ceilings.

SQUARE / FLANGE



ROUND / PLASTER FLANGE




IC/NIC/CCP



For projects requiring housings or IC rated fixtures.

1287 Hanger Bars comes standard with fixed and adjustable housing (see below for hanger bar dimensions).

FIXED C1/C2 Drivers




FIXED LUTRON / ELDO Drivers



PAN



For new construction applications not requiring a housing.

OPTION - New Pan





OPTION - Dropped Pan

for use in Armstrong® T-Bar ceilings



OPTION - Bracket Pan



1287 Hanger Bar comes standard with Bracket Pan & IC/NIC

Maximum Extension: 26"

